

# **smallantimagmas**

**A library of antiassociative magmas of  
small order**

**0.3.0**

4 January 2025

**Kamil Zabielski**

**Kamil Zabielski**

Address: Department of Theoretical Computer Science  
Białystok University of Technology  
Wiejska 45A  
15-325 Białystok  
Poland

## Copyright

© 2024 by Kamil Zabielski

smallantimagmas package is free software; you can redistribute it and/or modify it under the terms of the [GNU General Public License](#) as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

## Acknowledgements

We appreciate very much all past and future comments, suggestions and contributions to this package and its documentation provided by **GAP** users and developers.

# Contents

<b>1</b>	<b>smallantimagmas automatic generated documentation</b>	<b>4</b>
1.1	smallantimagmas automatic generated documentation of properties . . . . .	4
1.2	smallantimagmas automatic generated documentation of attributes . . . . .	7
1.3	smallantimagmas automatic generated documentation of global functions . . . . .	9
1.4	smallantimagmas automatic generated documentation of methods . . . . .	12
	<b>Index</b>	<b>14</b>

# Chapter 1

## smallantimagmas automatic generated documentation

### 1.1 smallantimagmas automatic generated documentation of properties

#### 1.1.1 IsAntiassociative (for IsMagma)

▷ `IsAntiassociative( $M$ )` (property)

**Returns:** true or false

identifies whether magma  $M$  is antiassociative.

Example

```
gap> IsAntiassociative(OneSmallGroup(16));  
false  
gap> IsAntiassociative(OneSmallAntimagma(2));  
true  
gap> IsAntiassociative(OneSmallAntimagma(3));  
true
```

#### 1.1.2 IsLeftCyclic (for IsMagma)

▷ `IsLeftCyclic( $M$ )` (property)

**Returns:** true or false

if magma is left cyclic  $m$ .

#### 1.1.3 IsRightCyclic (for IsMagma)

▷ `IsRightCyclic( $M$ )` (property)

**Returns:** true or false

if magma is left cyclic  $m$ .

#### 1.1.4 IsLeftCancellative (for IsMagma)

▷ `IsLeftCancellative( $M$ )` (property)

**Returns:** true or false

if magma is left cancellative  $m$ .

## Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> Display( MultiplicationTable(M) );
[ [ 2, 1 ],
  [ 2, 1 ] ]
gap> IsRightCancellative(M);
false
gap> IsLeftCancellative(M);
true
gap> List(AllSmallAntimagma(2), M -> IsLeftCancellative(M));
[ true, false ]
```

### 1.1.5 IsRightCancellative (for IsMagma)

- ▷ IsRightCancellative( $M$ ) (property)  
**Returns:** true or false  
 if magma is right cancellative  $m$ .

## Example

```
gap> List(AllSmallAntimagma(2), M -> IsRightCancellative(M));
[ false, true ]
```

### 1.1.6 IsCancellative (for IsMagma)

- ▷ IsCancellative( $M$ ) (property)  
**Returns:** true or false  
 if magma is cancellative  $m$ .

## Example

```
gap> List(AllSmallAntimagma(2), M -> IsCancellative(M));
[ false, false ]
```

### 1.1.7 IsLeftFPFInducted (for IsMagma)

- ▷ IsLeftFPFInducted( $M$ ) (property)  
**Returns:** true or false  
 is a left-hand sided fixed-point free inducted  $m$ .

## Example

```
gap> Display( MultiplicationTable( SmallAntimagma(2, 2) ) );
[ [ 2, 2 ],
  [ 1, 1 ] ]
gap> IsLeftFPFInducted( SmallAntimagma(2, 2) );
true
```

### 1.1.8 IsRightFPFInducted (for IsMagma)

- ▷ IsRightFPFInducted( $M$ ) (property)  
**Returns:** true or false  
 is a right-hand sided fixed-point free inducted  $m$ .

## Example

```
gap> Display( MultiplicationTable( SmallAntimagma(2, 1) ) );
[ [ 2, 1 ],
  [ 2, 1 ] ]
gap> IsRightFPFInducted( SmallAntimagma(2, 1) );
true
```

### 1.1.9 IsLeftDerangementInducted (for IsMagma)

▷ IsLeftDerangementInducted( $M$ ) (property)

**Returns:** true or false

is a left-hand sided derangement inducted  $m$ .

## Example

```
gap> M := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> IsLeftFPFInducted(M);
true
gap> IsRightFPFInducted(M);
false
gap> IsRightDerangementInducted(M);
false
```

### 1.1.10 IsRightDerangementInducted (for IsMagma)

▷ IsRightDerangementInducted( $M$ ) (property)

**Returns:** true or false

is a right-hand sided derangement inducted  $m$ .

## Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> IsLeftFPFInducted(M);
false
gap> IsRightFPFInducted(M);
true
gap> IsRightDerangementInducted(M);
true
```

### 1.1.11 IsLeftAlternative (for IsMagma)

▷ IsLeftAlternative( $M$ ) (property)

**Returns:** true or false

is a left-alternative magma  $M$ .

## Example

### 1.1.12 IsRightAlternative (for IsMagma)

▷ IsRightAlternative( $M$ ) (property)

**Returns:** true or false

is a right-alternative magma  $M$ .

---

Example

---

## 1.2 smallantimagnas automatic generated documentation of attributes

### 1.2.1 AssociativityIndex (for IsMagma)

▷ AssociativityIndex( $M$ ) (attribute)

identifies associativity index of  $M$ .

Example

```
gap> OneSmallAntimagma(2);
<magma with 2 generators>
gap> AssociativityIndex(OneSmallAntimagma(2));
0
gap> OneSmallGroup(4);
<pc group of size 4 with 2 generators>
gap> AssociativityIndex(OneSmallGroup(4));
64
gap> AssociativityIndex(OneSmallGroup(4)) = 4 ^ 3;
true
```

### 1.2.2 DiagonalOfMultiplicationTable (for IsMagma)

▷ DiagonalOfMultiplicationTable( $M$ ) (attribute)

computes diaognal of multiplication table of  $M$ .

Example

```
gap> List(AllSmallAntimagnas(3), M -> DiagonalOfMultiplicationTable((M)));
[ [ 2, 1, 1 ], [ 2, 1, 1 ],
  [ 2, 3, 2 ], [ 2, 1, 1 ],
  [ 2, 1, 1 ], [ 2, 1, 2 ],
  [ 2, 3, 2 ], [ 2, 1, 2 ],
  [ 2, 3, 1 ], [ 2, 3, 1 ]
]
```

### 1.2.3 CommutativityIndex (for IsMagma)

▷ CommutativityIndex( $M$ ) (attribute)

identifies commutativity index of  $M$ .

Example

### 1.2.4 AnticommutativityIndex (for IsMagma)

▷ AnticommutativityIndex( $M$ ) (attribute)

calculates anticommutativity index of  $M$ .

Example

### 1.2.5 SquaresIndex (for IsMagma)

▷ `SquaresIndex( $M$ )` (attribute)

computes squares index of  $M$  so the order of  $\{m^2 | m \in M\}$ .

Example

```
gap> List(AllSmallAntimagmas(2), M -> List(M, m -> m * m) );
[ [ m2, m1 ], [ m2, m1 ] ]
gap> List(AllSmallAntimagmas(2), M -> SquaresIndex(M ));
[ 2, 2 ]
gap> List(AllSmallAntimagmas(3), M -> SquaresIndex(M ));
[ 2, 2, 2, 2, 2, 2, 2, 2, 2, 3, 3 ]
```

### 1.2.6 IdSmallAntimagma (for IsMagma)

▷ `IdSmallAntimagma( $M$ )` (attribute)

identifies class of antiassociative magma  $M$ .

Example

```
gap> IsAntiassociative(OneSmallGroup(16));
false
gap> IsAntiassociative(OneSmallAntimagma(2));
true
gap> IsAntiassociative(OneSmallAntimagma(3));
true
```

### 1.2.7 LeftOrder (for IsExtLElement)

▷ `LeftOrder( $[m]$ )` (attribute)

returns a left order of element  $m$ .

### 1.2.8 RightOrder (for IsExtRElement)

▷ `RightOrder( $[m]$ )` (attribute)

returns a right order of element  $m$ .

### 1.2.9 LeftOrdersOfElements (for IsMagma)

▷ `LeftOrdersOfElements( $[m]$ )` (attribute)

returns a left order of element  $m$ .

### 1.2.10 RightOrdersOfElements (for IsMagma)

▷ `RightOrdersOfElements( $[m]$ )` (attribute)

returns a left order of element  $m$ .



## 1.3 smallantimagmas automatic generated documentation of global functions

### 1.3.1 AllSubmagmas

▷ AllSubmagmas( $M$ ) (function)

builds a collection of non-isomorphic submagmas of  $M$ .

Example

```
gap> AllSmallAntimagmas(2);
[ <magma with 2 generators>, <magma with 2 generators> ]
gap> List(AllSmallAntimagmas(2), M -> AllSubmagmas(M));
[ [ <magma with 1 generator> ], [ <magma with 1 generator> ] ]
```

### 1.3.2 MagmaIsomorphismInvariantsMatch

▷ MagmaIsomorphismInvariantsMatch( $M$ ) (function)

computes isomorphism invariants of  $M$ .

### 1.3.3 IsMagmaIsomorphic

▷ IsMagmaIsomorphic( $M$ ,  $N$ ) (function)

identifies whether magmas  $M$ ,  $N$  are isomorphic.

Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> T := MagmaByMultiplicationTable([ [2, 1], [2, 1] ]);
<magma with 2 generators>
gap> IsMagmaIsomorphic(M, M);
true
gap> IsMagmaIsomorphic(M, T);
true
gap> IsMagmaIsomorphic(M, N);
false
```

### 1.3.4 IsMagmaAntiisomorphic

▷ IsMagmaAntiisomorphic( $[M, N]$ ) (function)

identifies whether magmas  $M$ ,  $N$  are antiisomorphic.

Example

```
gap> N := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
```

```

gap> N := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> IsMagmaAntiisomorphic(M, M);
false
gap> IsMagmaAntiisomorphic(M, N);
true
gap> IsMagmaAntiisomorphic(M, TransposedMagma(M));
true

```

### 1.3.5 TransposedMagma

▷ `TransposedMagma([M])` (function)

generates transposed magma  $M$ .

Example

```

gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> IsMagmaAntiisomorphic(M, TransposedMagma(M));
true
gap> IsMagmaIsomorphic(M, TransposedMagma(TransposedMagma(M)));
true
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> Display(MultiplicationTable(M));
[ [ 2, 1 ],
  [ 2, 1 ] ]
gap> Display(MultiplicationTable(TransposedMagma(M)));
[ [ 2, 2 ],
  [ 1, 1 ] ]

```

### 1.3.6 LeftPower

▷ `LeftPower([m, k])` (function)

returns a left  $k$ -power of element  $m$ .

### 1.3.7 RightPower

▷ `RightPower([m, k])` (function)

returns a right  $k$ -power of element  $m$ .

### 1.3.8 AllSmallAntimagnas

▷ `AllSmallAntimagnas(n)` (function)

returns all antiassociative magmas of specified size  $n$  (a number)

## Example

```
gap> AllSmallAntimagmas(2);
[ <magma with 2 generators>, <magma with 2 generators> ]
gap> AllSmallAntimagmas(3);
[
  <magma with 3 generators>, <magma with 3 generators>, <magma with 3 generators>,
  <magma with 3 generators>, <magma with 3 generators>, <magma with 3 generators>,
  <magma with 3 generators>, <magma with 3 generators>,
  <magma with 3 generators>, <magma with 3 generators>
]
```

### 1.3.9 NrSmallAntimagmas

▷ NrSmallAntimagmas( $n$ ) (function)

counts number of antiassociative magmas of specified size  $n$  (a number).

## Example

```
gap> NrSmallAntimagmas(2);
2
gap> NrSmallAntimagmas(3);
10
gap> NrSmallAntimagmas(4);
17780
```

### 1.3.10 SmallAntimagma

▷ SmallAntimagma( $n$ ,  $i$ ) (function)

returns antiassociative magma of id  $[n, i]$ .

## Example

```
gap> SmallAntimagma(2, 1);
<magma with 2 generators>
gap> SmallAntimagma(4, 5);
<magma with 4 generators>
```

### 1.3.11 OneSmallAntimagma

▷ OneSmallAntimagma( $n$ ) (function)

returns a random antiassociative magma of size  $n$ .

## Example

```
gap> OneSmallAntimagma(2);
<magma with 2 generators>

gap> OneSmallAntimagma(3);
<magma with 3 generators>
```

### 1.3.12 ReallyAllSmallAntimagmas

▷ ReallyAllSmallAntimagmas( $n$ ) (function)

returns really-all antiassociative magmas, isomorphic, of specified size  $n$  (a number)

Example

```
gap> ReallyAllSmallAntimagmas(2);
[ <magma with 2 generators>, <magma with 2 generators> ]
```

### 1.3.13 ReallyNrSmallAntimagmas

▷ ReallyNrSmallAntimagmas( $n$ ) (function)

counts number of antiassociative magmas of specified size  $n$  (a number)

Example

```
gap> ReallyNrSmallAntimagmas(3);
52
```

### 1.3.14 AntimagmaGeneratorPossibleDiagonals

▷ AntimagmaGeneratorPossibleDiagonals( $n$ ) (function)

returns all possible diagonals of multiplication table for  $[n]$ -antimagma.

Example

```
gap> AntimagmaGeneratorPossibleDiagonals(2);
[ [ 2, 1 ] ]
gap> AntimagmaGeneratorPossibleDiagonals(3);
[
  [ 2, 1, 1 ], [ 2, 1, 2 ], [ 2, 3, 1 ], [ 2, 3, 2 ],
  [ 3, 1, 1 ], [ 3, 1, 2 ], [ 3, 3, 1 ], [ 3, 3, 2 ]
]
```

### 1.3.15 AntimagmaGeneratorFilterNonIsomorphicMagmas

▷ AntimagmaGeneratorFilterNonIsomorphicMagmas( $Ms$ ) (function)

filters non-isomorphic magmas  $m$ .

## 1.4 smallantimagmas automatic generated documentation of methods

### 1.4.1 MagmaIsomorphism (for IsMagma, IsMagma)

▷ MagmaIsomorphism( $M$ ,  $N$ ) (operation)

computes an isomorphism between magmas  $M$ ,  $N$ .

## Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := MagmaByMultiplicationTable([ [2, 1], [2, 1] ]);
<magma with 2 generators>
gap> MagmaIsomorphism(M, N);
<mapping: Domain([ m1, m2 ]) -> Domain([ m1, m2 ]) >
```

### 1.4.2 MagmaAntiisomorphism (for IsMagma, IsMagma)

▷ MagmaAntiisomorphism( $M$ ,  $N$ )

(operation)

creates an antiisomorphism between magmas  $M$ ,  $N$ .

## Example

```
gap> M := SmallAntimagma(2, 1);
<magma with 2 generators>
gap> N := SmallAntimagma(2, 2);
<magma with 2 generators>
gap> MagmaAntiisomorphism(M, N);
<mapping: Domain([ m1, m2 ]) -> Domain([ m1, m2 ]) >
```

# Index

AllSmallAntimagmas, [10](#)  
AllSubmagmas, [9](#)  
AnticommutativityIndex  
    for IsMagma, [7](#)  
AntimagmaGeneratorFilterNonIsomorphic-  
    Magma, [12](#)  
AntimagmaGeneratorPossibleDiagonals, [12](#)  
AssociativityIndex  
    for IsMagma, [7](#)  
CommutativityIndex  
    for IsMagma, [7](#)  
DiagonalOfMultiplicationTable  
    for IsMagma, [7](#)  
IdSmallAntimagma  
    for IsMagma, [8](#)  
IsAntiassociative  
    for IsMagma, [4](#)  
IsCancellative  
    for IsMagma, [5](#)  
IsLeftAlternative  
    for IsMagma, [6](#)  
IsLeftCancellative  
    for IsMagma, [4](#)  
IsLeftCyclic  
    for IsMagma, [4](#)  
IsLeftDerangementInducted  
    for IsMagma, [6](#)  
IsLeftFPFInducted  
    for IsMagma, [5](#)  
IsMagmaAntiisomorphic, [9](#)  
IsMagmaIsomorphic, [9](#)  
IsRightAlternative  
    for IsMagma, [6](#)  
IsRightCancellative  
    for IsMagma, [5](#)  
IsRightCyclic  
    for IsMagma, [4](#)  
IsRightDerangementInducted  
    for IsMagma, [6](#)  
IsRightFPFInducted  
    for IsMagma, [5](#)  
LeftOrder  
    for IsExtLElement, [8](#)  
LeftOrdersOfElements  
    for IsMagma, [8](#)  
LeftPower, [10](#)  
License, [2](#)  
MagmaAntiisomorphism  
    for IsMagma, IsMagma, [13](#)  
MagmaIsomorphism  
    for IsMagma, IsMagma, [12](#)  
MagmaIsomorphismInvariantsMatch, [9](#)  
NrSmallAntimagmas, [11](#)  
OneSmallAntimagma, [11](#)  
ReallyAllSmallAntimagmas, [12](#)  
ReallyNrSmallAntimagmas, [12](#)  
RightOrder  
    for IsExtRElement, [8](#)  
RightOrdersOfElements  
    for IsMagma, [8](#)  
RightPower, [10](#)  
SmallAntimagma, [11](#)  
SquaresIndex  
    for IsMagma, [8](#)  
TransposedMagma, [10](#)